

GENERAL PURPOSE CONTAINER



Suitable for any general cargo

	Maximum Inside Dimensions			Door Oper	ing	Tare Weight	Cubic Capacity	Maximum Payload
	Length	Width	Height	Width	Height	(kg/lbs)	(m/cu.ft)	(kg/lbs)
20' Dry Freight Container	5.895 m	2.350 m	2.392 m	2.340 m	2.292 m	2,250 kg	33.2 m ³	28,230 kg
	19'4 1/8"	7'8 1/2"	7'10 1/8"	7'8 1/8"	7'6 1/4"	4,960 lbs	1,172 cu.ft	62,240 lbs
40' Dry Freight Container	12.029 m	2.350 m	2.392 m	2.234 m	2.292 m	3,780 kg	67.7 m ³	26,700 lbs
	39'5 1/2"	7'8 1/2"	7'10 1/8"	7'8 1/2"	7'6 1/4"	8,330 lbs	2,390 cu.ft	58,870 lbs

HIGH CUBE GENERAL PURPOSE CONTAINER



Speciality for light, voluminous cargoes or those for excessive height(up to 2.56m).

	Maximum Inside Dimensions			Door Open	ing	Tare Weight	Cubic Capacity	Maximum Payload
	Length	Width	Height	Width	Height	(kg/lbs)	(m³/cu.ft)	(kg/lbs)
40' High Cube Container	12.024 m	2.350 m	2.697 m	2.350 m	2.697 m	4,020 kg	76.3³ m	26,460 kg
	39'5 3/8"	7'5 1/2"	8'10 1/8"	7′5 1/2″	8'10	8,860 lbs	2,694 cu.ft	58,340 lbs
45' High Cube Container	13.582 m	2.347 m	2.690 m	2.347 m	2.690 m	4,110 kg	85.7 ³ m	28,390 lbs
	44'2 1/2"	7'8 1/4"	8″10″	7'8 1/4"	8″10″	9,061 lbs	3,026 cu.ft	62,589 lbs

OPEN TOP CONTAINER



Especially for overweight cargo, loading from top side eg: crane, loading from door side: eg- with cargo hanging from overhead tackle.

	Maximum Inside Dimensions				Top Openin	ng	Tare Weight	Cubic Capacity	Maximum Payload
	Length	Width	Middle	Side	Length	Width	(kg/lbs)	(m ³ /cu.ft)	(kg/lbs)
20' Open Top Container	5.895 m	2.350 m	2.394 m	2.364 m	5.895 m	2.350 m	2,100 kg	32.45 m ³	21,900 kg
	19'4"	7'8 1/2"	7'10 1/4"	7′ 9″	19'4"	8' 1/2"	4,630 lbs	1,145 cu.ft	48,280 lbs
40' Open Top Container	12.023 m	2.335 m	2.378 m	2.318 m	12.023 m	2.335 m	3,800 kg	66.7 m ³	26,680 lbs
	39'5 3/8"	7′8″	7'9 5/8"	7'7 1/4"	39'5 3/8"	7/8"	8,380 lbs	2,354 cu.ft	58,820 lbs

FLAT TOP CONTAINER



Specially for Heavy Lifts and over width cargoes. Strong bottom construction with fixed endwalls. (which allows bracing and lashing of cargoes as well as stacking)

	Maximum Inside Dimensions			Door Opening		Top Opening		Tare Weight	Cubic Capacity	Maximum Payload
	Length	Width	Height	Width	Height	Length	Width	(kg/lbs)	(m³/cu.ft)	(kg/lbs)
20' Flat Rack Container	5.625 m	2.208 m	2.172m					2,800 kg		21200 kg
	18'5 3/8"	7'2 7/8"	7'1 1/2"					6,170 lbs		46,740 lbs
40' Flat Rack Container	11.712 m	2.322 m	1.981 m					4,750 kg		26,730 lbs
	39'5 3/8"	7"8 7/8"	6'6"					10,470 lbs		56,730 lbs
40' Collapsible Flat Rack	11.660 m	2.200 m	2.245 m					5,700 kg		39,300 kg
	38'3 1/8"	7"2 5/8"	7'4 3/8"					12,570 lbs		86,640 lbs



Disclaimer: While we assume that the information and content provided by us is true and correct, it may, nevertheless, contain errors or inaccuracies. Affinity Logistics does not assume any liability for the accuracy of the information and content provided in the brochure, or for the consequences resulting from using the information and con-tent provided in the brochure. Affinity Logistics does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made.

